



AT A GLANCE

- Real 1000W RMS with accurate deep tones
- CELTO woofer with trimmed chassis for ultra compact format
- Birch plywood cabinet with smooth texture or varnish finish
- High Efficiency for incredible SPL to Size ratio
- 8 M8 Flying points for added versatility
- Available in Black, White, Natural and Oak colors

SPECIFICATIONS

Power handling (AES Standard)	1000W RMS / 4000W Peak
Nominal impedance	8 Ohm
Frequency response (-6dB half space, no EQ)	38~1200Hz
Manufacturing Consistency tolerance	±2dB from 50 to 400Hz
Average Sensitivity (wideband 200~16000Hz)	99dB/W/m
Calculated Maximum SPL / 1m	129dB continuous / 135dB Peak
Nominal Directivity (-6dB)	omnidirectional in usage range
Recommended low cut filter	30Hz 24dB/oct
Low Frequency driver	Custom 17.5" CELTO Acoustique Ferrite Magnet, 3.6" Voice coil
Crossover	No. Must use external DSP or dedicated iFIX amplifiers
Flying hardware	8 M8 points
Connectors	Phoenix connector
Cabinet	CNC made with tongue and groove assembly 18 mm birch plywood
Finish	Smooth textured coating (Black and White colors) or Varnish finish (Natural and Oak colors)
Size (HxWxD)	482X596X600mm
Weight	32kg net / 38kg gross