



Real 3600W RMS power capacity (8 hours pink noise)

Clean and deep reproduction

Replace universal dual 18s with added SPL

Premium custom made CELTO Acoustique European Driver

Heavy braced, vibration free birch plywood cabinet

Touring grade gloss-free black painting

Applications

CSW221 subwoofer is suitable for bass reinforcement for main PA systems, touring or permanent installations for small to large stages, indoor or outdoor live performances.

Suitable for:

FoH / Multi-functional room/ Auditorium and Theater / Nightclub / Pub & Bar / Commercial announcements

Specifications

Power Handling (AES standard)	3600W RMS / 7200W Program / 14400W Peak
Nominal impedance	4 ohms
Frequency response (-6dB no preset)	28-1000Hz
Average sensitivity	102dB / W / m
Maximum SPL (Calculated)	137dB continuous / 140dB Program / 143dB Peak
Nominal Directivity (-6dB)	Omni in usable range
Low Frequency Driver	21" CELTO ACOUSTIQUE 21EX1800 (2pcs)
Woofers Chassis	Die cast Aluminium
Woofers Voice coil diameter	4.5"/115 mm long throw WITH dcs COOLING SYSTEM
Crossover	No, active mode only
Floor monitor use	N/A
Flying hardware	No
Connectors	Genuine NEUTRIK 2pcs SpeakON NL4MP
Mounting hardware	2pcs M20 thread socket
Cabinet	Heavily braced Birch Plywood
Finish	Textured Waterbrone Black coating Acoustic PU foam behind Front grill
Size (WxHxD)	1226x588x805 mm net, 1380x710x915 mm gross
Weight	99Kg net, 112Kg gross