

- 800W RMS power capacity
- Proven performance and reliability
- Highly dynamic and holographic reproduction
- Premium in-house designed and made CELTO drivers
- HSP Annular ring radiator for smooth HF reproduction
- Proprietary 80°x50° 6th order Polynomial horn
- Textured Waterborne Black coating



Applications

CT15 G3 loudspeaker system is suitable for main PA reinforcement with or without subwoofer, portable system or permanent installation, monitor in stages, and delay fill.

FoH / Pub / Multi-functional Rooms / Auditoriums / Theatres / Commercial Applications / Nightclub

Specifications

Power Handling (AES standard)	800W RMS / 1600W / 3200W Peak
Nominal impedance	8 ohms
Average sensitivity	98dB / 1W / 1m
Maximum SPL (calculated)	128 dB RMS / 131dB Program / 134dB Peak
Frequency response (-6dB no preset)	48~22000Hz
Nominal directivity (-6dB)	80° (H) x 50° (V)
Cabinet material	Outdoor grade Birch Plywood
Cabinet finish	Textured Waterborne Black coating Integral Airnet fabric on Front grill
Floor monitor use	Yes, dual symmetric angle
Flying hardware	16 M8 points
Mounting hardware	Ø35mm socket (0° and 10°)
LF	15" CELTO ACOUSTIQUE 15PF800
Woofer Chassis	Die Cast Aluminum
Woofer Voice coil diameter	3.6" / 91mm
HF	CELTO ACOUSTIQUE ACD44
HF RMS power (AES standard)	80W above 1.2kHz
HF Exit	1" / 25mm
HF Voice coil diameter	1.7" / 44mm
HF Diaphragm	HSP Annular Ring Radiator
Crossover	1.4kHz 2-way passive network
Connectors	Genuine NEUTRIK 2pcs Speakon NL4MP
Speaker size / Shipping size (WxHxD)	445x710x414 mm / 545x820x520x mm
Weight	30kg net, 36kg gross